

ELECTRIC THERMAL DIRECT WIFI RADIATOR TECHNICAL DATA SHEET



MODELS

Código	Potencia (w)	Nº Elem	Dimensiones (mm)	Dimensiones Embalaje (mm)	Peso Neto (Kg)	Peso Bruto (Kg)
SOL0500WIDIR	500	3	335 x 580 x 95	391 x 641 x 126	7,0	7,62
SOL0750WIDIR	750	4	415 x 580 x 95	471 x 641 x 126	8,9	9,62
SOL1000WIDIR	1000	6	575 x 580 x 95	631 x 641 x 126	12,5	13,5
SOL1500WIDIR	1500	9	815 x 580 x 95	871 x 641 x 126	17,7	18,79
SOL1800WIDIR	1800	11	975 x 580 x 95	1031 x 641 x 126	21,3	22,54

CHARACTERISTICS

- Fluid radiator.
- Die-cast aluminium elements.
- Armoured steel heating element.
- Efficient consumption.
- Daily/weekly programming.
- Manual mode.
- Automatic mode (comfort, economic and anti-freeze).
- Open windows function.
- Early activation.
- Geolocation function.
- Invite users function.
- Keyboard lock.
- Consumption measurement.
- Power rationing.
- Temperature probe calibration.
- Temperature configurable in 0.5°C steps.
- NTC temperature sensor with 0.1°C accuracy.
- PID regulation.
- Voice control. Compatible with Amazon Alexa and Google Assistant.
- No multilink required

TECHNICAL DATA

Material	Aluminium
IP	20
Class	I
Power cable w/plug	1 m

Supply voltage	230 Vac 50Hz
Fixing kit w/template	Yes
Selectable setting range	5°C - 30°C
Safety thermal limiter	Yes

MINIMUM SAFETY DISTANCES

